

HUD ARD

Attack Resistant Door

Technical Overview



High Strength Attack Resistant Door

Resistant to sustained Sledge Hammer and Pinch Bar Attack, the ARD Door offers secure protection to secure areas like cash rooms, stock rooms and safe rooms.

Construction

- 50mm Solid Core Steel fully Clad Door
- 2mm Steel Cladding to attack side, 1.5mm Cladding to inside
- 300x300 5mm Steel Plate Lock Protection plate
- 5mm Steel angle frame
- Full length continuous stainless steel hinge
- 6 x 10mm Anti Lift pins protecting hinge
- Union 3R35 Mortice Lock with Duress Exit feature
- Frame fitted with PADDE ES2000 Electric Strike
- Union WS9 Door Eye Viewer

Locking

Union 3R35 Mortice Lock with Duress Exit feature
Frame fitted with PADDE ES2000 Electric Strike for easy connection to electronic access control system

Fixing to Door Cavity

The Door supplied fixed to its external frame, frame is squared up in the door cavity and internal frame bolts through the wall onto the external frame to lock the door into position.

Attack Tested

Attack tested to withstand a 3 Minute sustained sledge hammer attack and a 3 Minute sustained pinch bar attack.

Dimensions :

Clear opening of 937mm Wide x 2075mm High

Wall Cavity for Door Installation of 1020mm Wide x 2115mm High

To suit wall thickness of 90mm to 120mm

